

AEM ELECTROLYSER


With a capacity of 1 MW of electrical input, the new Ansaldo Green Tech electrolyser is conceived for applications with **large hydrogen production volumes**. The Ansaldo Green Tech 1MW electrolyser is based on last generation **Anion Exchange Membrane** and innovative formulation for the anodic and cathodic catalysts, which enable efficient and high-purity hydrogen production, limiting gas crossover, even at large scales.

In addition to high hydrogen production rate, the electrolyser is also designed to optimize efficiency, flexibility, safety, and reliability.

High efficiency is ensured by an accurate selection of catalyst materials and deposition techniques, FEM based internal geometry optimization, electrolyte flow design based on CFD calculations and proper sizing of the auxiliary equipment to limit the plant energy consumption.

Safety and Reliability are ensured by an extensive monitoring of all the critical parameters that are proof of proper operating regime, which are, among others, process temperatures and pressures, output gas quality and crossover phenomena. The electrical supply is managed with all appropriate safety systems for the quickest and safest emergency actions. The unit features advanced methods to limit membrane deformation and stress, decreasing its degradation rate.

The control system allows **fast and efficient transients**, with full **monitoring** of all relevant process parameters.



The electrolyser can be installed on a green or brownfield area. It is designed for **remote and unmanned operations**. The control system, in charge of acquisition, monitoring, and regulation of hydrogen production as well as plant operation, is designed to support the electrolyser flexibility to operate with a variable power input from the grid. In particular, the system is suitable to operate associated to **renewable energy sources** such as photovoltaic or wind energy.

The standard **installation** is modular, based on an outdoor containerized solution, but in case of multi-megawatt plant, dedicated open design solutions are envisaged.

Maintenance is minimal and dedicated service packages can be provided based on Customer needs, leveraging on remote monitoring and control of the main operational data.

Electrolyser performance

Single Stack power consumption (BoL)	1 MW
System power consumption	1.16 MW
Hydrogen production (base load)	21 kgH ₂ /h @30barg
Oxygen Production (base load)	168kg/h @0.3-30barg
Energy consumption	55 kWh/kgH ₂
Startup time (warm)	<2 min
Load range	30-100%
Demi water consumption	9,1 l/kgH ₂
Demi water quality	5µS/cm
Hydrogen quality	99,9% (higher purity achievable with dryer)
Operating temperature	-5 ÷ +40°C
Sound Pressure Level	85 dB(A)@1m
Container dimension	40' standard ISO



For more information,
please visit
www.ansaldoenergia.com

Follow us on LinkedIn 
[www.linkedin.com/company/
ansaldo-energia](https://www.linkedin.com/company/ansaldo-energia)



Ansaldo GreenTech, all rights reserved. Trademarks mentioned in this document are the property of Ansaldo GreenTech, its affiliates, or their respective owners in the scope of registration. The information contained in this document is merely indicative. No representation or warranty is provided, nor should be relied on, that such information is complete or correct or will apply to any particular project. This will depend on the technical and commercial circumstances. Said information is provided without liability and is subject to change without notice. Reproduction, use or disclosure to third parties, without express written authority, is strictly prohibited.